



RF28-70mm f/2L USM

- Constant f/2 aperture throughout the zoom range
- The highest standards of performance, operability & durability
- Lens control ring for fast intuitive shooting
- Built in Digital Lens Optimizer

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS

RF28-70mm F2 L USM

Optical Features/Specifications

Angle of view (horzntl, vertl, diagnl)	65°-29°, 46°-19°30', 75°-34°
Lens construction (elements/groups)	19/13
No. of diaphragm blades	9
Minimum aperture	f/2
Closest focussing distance (m)	0.39m
Maximum magnification (x)	0.09x (wide) - 0.18x (tele)
Distance Information	Via EVF or LCD
Air Sphere Coating (ASC)	YES
AF actuator	Ring USM

Physical Specifications

Dust/moisture resistance	Yes ¹
Filter diameter (mm)	95mm
Max. diameter x length (mm)	103.8mm x 139.8mm
Weight (g)	1430g

Accessories

Lens cap	E-95
Lens hood	EW-103
Lens case/pouch	LP1424
Rear cap	Lens Dust Cap RF
Magnification with Extension Tube EF12 II	Not supported
Magnification with Extension Tube EF25 II	Not supported
Extender Compatibility	Not supported

¹ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon