

RF35mm F1.8 MACRO IS STM

- 5 stop Image Stabilizer
- Lens control ring for fast intuitive shooting
- 9-blade circular aperture for exquisite soft-toned images
- Wide-angle macro lens with f/1.8 brightness and 0.5x magnification







TECHNICAL SPECIFICATIONS

Optical Fe	eatures/Specifications	
	Angle of view (horzntl, vertl, diagnl) Lens construction (elements/groups) No. of diaphragm blades Minimum aperture Closest focussing distance (m) Maximum magnification (x) Distance Information Coating	54°, 38°, 63° 11/9 9 f/1.8 0.17m 0.5x Via EVF or LCD Super Spectra Coating
	AF actuator	Gear-type STM
Physical S	pecifications	
	Dust/moisture resistance Filter diameter (mm) Max. diameter x length (mm) Weight (g)	No 52mm 74.4mm x 62.8mm 305g
Accessori	es	
	Lens cap Lens hood Lens case/pouch Rear cap Magnification with Extension Tube EF12 II Magnification with Extension Tube EF25 II Extender Compatibility	E-52 EW-52 (Sold separately) LP1016 (Sold separately) Lens Dust Cap RF Not supported Not supported Not supported

For more information visit canon.com.au canon.co.nz

