

Print and share your photos instantly with the exciting and colourful CP770. The bucket shaped storage case simplifies the hassle of preparing and storing the printer

The SELPHY CP770 makes printing and sharing photos instantly fun and simple. With the revolutionary new bucket shaped storage case, which stores all the printer accessories, preparing and storing the printer couldn't be more effortless. New Automatic red-eye correction and Portrait Image Optimize, means beautiful, lab quality images that print in less than 52sec. With no need for a computer and an optional battery pack, you can now share your photos with friends and family anywhere.

### Key Features

- Easy to use
- Integrated bucket shaped storage solution
- Huge 2.5" TFT colour LCD for viewing your images when printing directly from compatible memory cards
- Photo lab quality prints delivered in high speeds of approx 52 seconds<sup>1</sup>
- Automatic Red-Eye Correction
- Instantly dry overcoat
- Direct photo printing from compatible cameras & mobile phones using PictBridge & memory cards
- Wireless printing
- 100 year print life, 4 layer print process – cyan, magenta, yellow and a durable clear UV protective coating to prevent smudging, fading and colour change to ensure your precious memories last a lifetime



### Long Lasting Prints

Canon printing technology produces bright, vibrant prints that – if stored correctly in an album, will retain their colour and vibrancy for up to 100 years\*



### Perfect People Prints

People's faces are detected within the photograph, and the brightness is corrected for superb, natural-looking results



### Sharp Previews

2.5" TFT LCD screen for vivid bright and sharp images to view and share your photos



### Red-eye Correction

In-printer red-eye correction restores eyes to their natural look without the need for a computer



### Click-Connect-Print

Print photos directly from compatible digital cameras using PictBridge technology, no need for a PC<sup>2</sup>



### Ultra Fast

Say goodbye to waiting for your photos to arrive. The SELPHY CP770 can deliver lab-quality prints in as little as 52 seconds<sup>1</sup>



### Wireless Printing

Print photos directly from compatible mobile phones, using either built-in infrared connectivity or the optional Bluetooth adaptor



### Print Anywhere

With the addition of the optional battery, the SELPHY CP770 becomes a truly portable printer – perfect for holidays, the outdoors or anywhere

### SELPHY- Rediscover the joy of photo sharing

Canon SELPHY is a funky photo printing experience that makes sharing photos more enjoyable. The dye-sublimation printing technology with protective overcoat produces photo lab quality photos that will resist smudging and fading. The compact, portable design with no need for a computer is the easiest way to share photos instantly.

# SELPHY CP770

## Compact Photo Printer

**Canon**  
advanced simplicity®

### SELPHY ES2 Technical Specifications

#### Printer Functions

|   |  |  |                    |
|---|--|--|--------------------|
| Print Method  | Dye-sublimation thermal printer  |  |                    |
| Printing Resolution                                   | 300 x 600 dpi (max)  |  |                    |
| Gradation   | 3 colour inks with over coating, 256 levels per colour (24 bit colour depth)   |  |                    |
| Print Speed <sup>1</sup>                              | <b>Direct print – memory card, PictBridge, Canon Direct Print</b>  |  |                    |
|   | Postcard size:   | Approx. 52 sec. <sup>1</sup>   |                    |
|   | L size:  | Approx 43 sec. <sup>1</sup>  |                    |
|   | Card size (inc. label paper):  | Approx 25 sec. <sup>1</sup>  |                    |
| Ink   | Dedicated cartridge (Y, M, C, and overcoating) – Included with media   |  |                    |
| Paper   | Dedicated paper for Postcard size, L size, Card size, Card size (full size label sheets)   |  |                    |
| Print sizes   |  | <b>Borderless</b>  | <b>With Border</b> |
|   | Postcard size:   | 148.0 x 100.0 mm   | 121.9 x 91.4 mm    |
|   | L size:  | 119.0 x 89.0 mm  | 105.3 x 79.2 mm    |
|   | Card size (inc. label paper):  | 86.0 x 54.0 mm   | 66.7 x 50.0 mm     |
| Number of prints with optional battery pack (NB-CP2L) | Postcard size paper:   | Approx. 36 sheets or more  |                    |
|   | L size paper:  | Approx. 36 sheets or more  |                    |
|   | Card size paper:   | Approx. 72 sheets or more  |                    |
| Feeding System  | Automatic feed from paper cassette   |  |                    |
| Paper eject system                                    | Prints are ejected to the print receptacle at the top of printer   |  |                    |
| Printing Modes  | All image print, DPOF image print, Fixed Size Layout, ID Photo Print, Movie Print, Single Image Print, 2-up, 4-up and 8-up Layout, Index print <sup>2</sup>  |  |                    |
| Print Settings  | Image Optimize, Borderless, Bordered, Date Print, File Name Print, My Colours (5 modes), Red-Eye Correction <sup>6</sup>   |  |                    |
| Image Longevity                                       | 100 Years Print <sup>7</sup>   |  |                    |
| Camera Direct Printing                                | PictBridge compliant, Canon Direct Print compliant   |  |                    |
| Memory Card Printing                                  | Supported card types: Compact Flash, Memory Stick, Memory Stick PRO, Memory Stick PRO Duo, Memory Stick DUO, Microdrive, miniSD, mini SDHC, MMC, MMCplus, MMCmobile, SD, SDHC, RS-MMC, microSD2, microSDHC <sup>2</sup> MMCmicro <sup>2</sup> , Memory Stick micro <sup>2</sup> , xD-Picture Card <sup>2</sup> |  |                    |
| Camera Phone Printing                                 | Optional Bluetooth Unit BU-30 (printing from some mobile camera phones & PDA's) <sup>3</sup> , IrDA IR (printing from some mobile camera phones) <sup>4</sup> , IrSimple (printing from some mobile devices) <sup>5</sup>  |  |                    |
| Print from a Computer                                 | Yes, requires a standard USB cable. USB type B port on printer   |  |                    |
| Camera  | USB type A port on printer, WiFi IEEE 802.11b (with Digital IXUS WIRELESS and Wireless print adapter WA-1E)  |  |                    |
| <b>General Features</b>                               |  |  |                    |
| Colour LCD Screen                                     | 2.5" Colour TFT viewer   |  |                    |
| Operating System                                      | PC: Windows 2000 SP4/XP (SP2), Mac: OS.X (10.3.9 or later)   |  |                    |
| Included as Standard                                  | SELPHY ES2, Postcard size trial paper pack and ink cassette, Compact Power Adaptor CA-ES100, AC Cable, Canon Solution Disk, Cleaner Stick  |  |                    |
| Software Included                                     | PC: Zoombrowser EX, Photo Express LE. Mac: ImageBrowser  |  |                    |
| Power Supply & Battery Chargers                       | CA-CP200W Power Adaptor, Battery Pack NB-CP2L  |  |                    |
| Power Consumption                                     | Approx. 60W printing (standby: 4W)   |  |                    |
| Operating Environment                                 | 5-40 °C, 20 – 80% humidity   |  |                    |
| Min. Dimensions (W x D x H)                           | 248 x 156.4 x 77.3mm (printer only without protrusions)  |  |                    |
| Weight  | Approx. 1.06Kg (Excluding Ink / Paper Intergrated Cartridge)   |  |                    |
| Optional Accessories                                  | Paper/Ink Packs:   | Postcard (KP-36IP, KP-108IN ), L size (KL-36IP), Wide Size (KW-24IP), Credit Card (KC-36IP) and Credit Card Label stickers (KC-18IL) |                    |



#### Consumables



**All data based on Canon's Standard Test Method.**

#### Disclaimers

- Print speed can vary dependent on data size, print method, memory card and capacity and is measured from start of printing excluding paper handling
- Requires an adaptor
- Mobile phones and PDA's must be Bluetooth enabled and support Bluetooth version 1.1 or above Photo printing only – pictures must be in the JPEG format. Bluetooth operation depends on the device and software version used.
- Pictures must be taken in the JPEG format and transferred using the IrOBEX or IrMc by vNOTE protocol
- Modes / features available may differ dependent on camera model or use of memory card to print
- Modes / features available may differ dependent on camera model or use of memory card to print
- To test the image permanence of prints that are stored in an album, we use an accelerated testing method as how the image permanence of silver-halide photo papers are measured when stored in dark places. Print samples are printed with the optical density of 1.0 (each Bk, C, M, Y). The samples are kept in a certain environment of high temperature and 50% humidity. The rate of the decrease in the optical density and rate of yellow discoloration are recorded. The recorded results are then converted to the length of time when print image is kept in an environment of 23°C/ 50% humidity. (Criteria for estimation of print longevity) The point where monochromatic/ reflective optical density shows loss of 30% (starting density of 1.0).