



EF 70-200MM f/4L IS II USM

- Compact & lightweight super telephoto lens
- 5-stop image Stabilizer for sharp handheld shooting
- 3x Image Stabilizer modes for ultimate control

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS

EF 70-200MM f/4L IS II USM

Optical Features/Specifications

Angle of view (horzntl, vertl, diagnl)	29°-10°, 19°30'-7°, 34°-12°
Lens construction (elements/groups)	20/15
No. of diaphragm blades	9
Minimum aperture	32
Closest focussing distance (m)	1.0
Maximum magnification (x)	0.27 (tele)
Distance Information	Yes
AF actuator	Ring USM ¹

Physical Specifications

Dust/moisture resistance ²	Yes
Filter diameter (mm)	72
Max. diameter x length (mm)	80 x 176
Weight (g)	780

Accessories

Lens cap	E-72II
Lens hood	ET-78B
Lens case/pouch	LP1224
Rear cap	Lens Dust Cap E
Magnification with Extension Tube EF12 II	0.16-0.25
Magnification with Extension Tube EF25 II	0.37-0.43
Extender Compatibility	Yes

¹ Full time Manual focus

² Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon