

LV-WX370

**Bright and portable projector
with LCD technology for excellent
colour and detail**



HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

CRESTRON
connected

PJLink™

Canon

- Compact, lightweight design making it easy to be carried
- LCD technology for excellent 10-bit colour reproduction
- High brightness and high contrast providing bright, vivid images
- Up to 20,000 hours lamp life lowers total cost of ownership and limits maintenance time
- Immediate power off so can be moved or stored away quickly
- Low running noise of 30 dB in eco mode for distraction-free use
- Multiple connectivity options including HDMI, USB viewer function, RS232-C and LAN
- Corner keystone correction plus pincushion / barrel distortion correction*, ensures geometry stays accurate
- 10W speaker for incorporating audio into the room



Technical Specifications

Model		LV-WX370
Panel	Type	LCD x 3
	Size and Number	0.59" LCD x 3
	Aspect Ratio	16:10
	Native Resolution	1280 x 800 (WXGA), 1,024,000 pixels
Optics	Lamp Type	Super high pressure lamp
	Lens F Number and Focal Length	F1.6 – F1.76; f=19.2 – 23.0mm
	Zoom Magnification and Control	1.2x Manual
	Electrical zoom	1.6x max
	Focus Control	Manual
Image and audio	Brightness	3700 lumens (Eco: 2405 Lumens)
	Brightness Uniformity	80%
	Contrast Ratio	15,000:1 (Fully white : fully black. Iris on, lamp mode normal)
	Projection Distance Coverage	0.94m – 11.60m
	Distance for 100" Image	3.20m - 3.85m
	Screen Size	30-300" (65x40 - 646x404cm)
	Projection Ratio	1.48 - 1.78:1
	Keystone Correction Range	Vertical: +/-30° Horizontal: +/-15°
	Digital PC Input	WUXGA / FHD / WSXGA+ / UXGA / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA / Mac16
	Analogue PC Input	WUXGA / FHD / WSXGA+ / UXGA / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA / Mac16
	Digital Video Input	1080p / 1080i / 720p / 576p / 480p / 576i / 480i
	Component Video input	1080p / 1080i / 720p / 576p / 480p / 576i / 480i
	Composite Video input	NTSC / NTSC4.43 / PAL60 / PAL-M / PAL / PAL-N / SECAM
Display Modes	Standard, Presentation, User image, Colourboard, Blackboard (Green) & Movie	
Built-in Speaker	10W monaural	
Ports and connectors	Analogue PC Input	Mini Dsub 15
	Analogue PC Output (Monitor out)	Mini Dsub 15
	Digital PC / Digital Video	HDMI x 2
	Audio Input 1	RCA phono x 2
	Audio Input 2	3.5mm stereo mini-jack
	Audio Output	3.5mm stereo mini-jack
	USB	Type A still image: JPG/GIF/PNG/TIF/BMP. Movie: AVI. PDF
	Mini USB Service Port	Type B. Firmware update and PC screen transfer*
	Projector Control	Mini D-Sub 9-pin (RS232c)
	Network Port 1	RJ-45 (100Base-TX / 10Base-T). PC screen transfer*

Technical Specifications

Model		LV-WX370
Mechanisms	Front Elevation Mechanism	2 x rotary feet (up to 10° elevation angle). Extension length 42mm
	Rear Elevation Mechanism	2 x fixed feet
Ratings	Dimensions (W x H x D)	345mm x 261mm x 99mm (including protrusions)
	Weight	3.2kg
	Power Source	100-240 V AC, 50/60Hz
	Power Consumption	310W / Eco: 217W
	Light source life	Normal: 10,000h / Eco: 20,000h
	Noise Level	Normal / Eco: 37/30 dB
	Operating Environment	0° to 40°C (RH: 10-85%)
Storage Environment	-20°C to +60°C	