

# XEED WUX500

**Compact, high brightness projector  
model with WUXGA resolution**



Powerful, Consistent  
5000lm Brightness



Easy HDBaseT Setup  
and Cost Savings



Wireless LAN  
Convenience



Precise Imaging  
Capabilities and  
Correction



Simple PC-less Usage

**Canon**

- Achieve detailed, ultra-realistic images with native WUXGA resolution (1920 x 1200 pixels) and Full HD capability
- Enjoy a vivid 5000 lumens constant\* brightness and native 2000:1 contrast ratio
- Create smooth, seamless images with vivid, accurate colours using LCOS panel and AISYS technology
- 1.8x zoom lens with manual lens shift, zoom and focus for fast and accurate installation
- Connect to a wide variety of devices thanks to HDBaseT connection\*\* and Wi Fi for wireless LAN with Network Multi Projection (NMPJ)
- Advanced imaging features include hardware edge blending, picture-by-picture and four corner keystone correction
- PC-free multi projection via USB using up to nine projectors
- HDMI and RJ-45 network ports
- Easy access to the lamp and air filter helps keep maintenance costs down
- Energy efficient with up to 5000h lamp life and only 30 dBA in ECO mode



\*1 Might not display at the expected resolution when some input devices are connected

\*2 This projector doesn't support "Extron XTP" feature.

# Technical Specifications

Model		XEED WUX500
Panel	Type	LCOS reflective display, TFT Active Matrix
	Size and Number	0.71" diagonal, 3 panels
	Aspect Ratio	16:10
	Native Resolution	1920 x 1200 (WUXGA), 2,304,000 pixels
Optics	Lamp Type	250W NSHA
	Lens F Number and Focal Length	F2.8; f=21.7 - 39.0mm
	Zoom Magnification and Control	1.8x Manual
	Focus Control	Manual
	Lens Shift	Vertical: 0% to +60%, Manual Horizontal: +/- 10%, Manual
Image and audio	Brightness	5000 lumens (3800 lumens in Eco Mode)
	Brightness Uniformity	90%
	Contrast Ratio	2000:1 (full on / full off)
	Projection Distance Coverage	1.2m - 16.2m (3.0m - 5.4m for 100" image)
	Screen Size	40" - 300" (86 x 54cm - 646 x 404cm)
	Throw Ratio	1.39 - 2.51 : 1
	Keystone Correction Range	V: +/-20° H: +/-20°
	Digital RGB Compatibility	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
	Analogue RGB Compatibility	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
	Digital Video Scan Systems	1080p / 1080i / 720p / 576p / 480p
	Component Video Scan Systems	1080p / 1080i / 720p / 576p / 576i / 480p / 480i
	Supported File Types	JPEG still image
	Built-in Speaker	5.0W RMS, Monaural
Ports and connectors	Digital RGB Input	DVI-I 29-pin (shared)
	Digital Video and Audio Input	HDMI (with Deep Colour)
	Analogue RGB Input 1	DVI-I 29-pin (shared)
	Analogue RGB Input 2	Mini D-Sub 15-pin (Component via optional adaptor cable)
	Audio Input 1	3.5mm stereo mini-jack
	Audio Input 2	3.5mm stereo mini-jack
	Audio Output	3.5mm stereo mini-jack (variable level)
	USB Port	USB Type A
	Service Port / Projector Control	Mini D-Sub 9-pin
	Network Port	RJ-45 (HDBaseT / 1000BASE-T / 100BASE-TX / 10BASE-T)
	Wired Remote Control	3.5mm stereo mini-jack

# Technical Specifications

Model		XEED WUX500
Mechanisms	Front Elevation Mechanism	Two rotary feet, 6° maximum image elevation
Ratings	Dimensions (W x H x D)	337mm x 136mm x 370mm
	Weight	5.9kg
	Power Source	100-240 V AC, 50/60Hz
	Power Consumption	Normal Mode: 365W / Eco Mode: 295W / Standby: 1.3W / Standby (LAN & HDBaseT off): 0.2W
	Noise Level	Normal Mode: 37dBA / Eco Mode 30dBA
	Operating Environment	5°-40°C
	Storage Environment	-5°C to +60°C
	Video	HDMI1.4(EDID,HDCP)
	Audio	Via HDMI HDBaseT/HDMI PbyP projection not possible.
	Ethernet	Fall back function is not supported
	Control	RS-232C
	Power	Not supported Power supply to projector is not supported.