

PIXMA HOME TS6260

Dependable All-In-One Home Printer



Wireless

Print with ease with PIXMA Cloud Print and other applications such as Apple AirPrint, Google Cloud Print that simply connect to mobile devices.



Print With New Media

Get creative and use your printer to print on a variety of new mediums such as $5" \times 5"$ and $3.5" \times 3.5"$ square sizes, restickable and magnetic paper.



Message in Print

Personalise your photos further with the ability to add messages to your photos. This involves adding add, frames and other decorations to your images or videos.



5 Individual Inks

Print high resolution photos and media with 5 colour individual inks.



Dual Paper Feeder

Get flexible with the way your printer receives paper — either through rear paper feeding or via front paper cassette.



Auto 2-sided printing

Save time and money with the auto duplex printing function, which automatically prints on both sides of paper.



Document Removal Reminder If you happen to leave your important documents in the flatbed scanner, this smart printer will remind you to remove your document with an alert.



Borderless Printing

The borderless printing function allows you to print data without any margin by enlarging the data so that it extends slightly off the paper. Borderless photo printing has been improved to approximately 21 seconds for one 4"x6" photo.

What inks can I use with my printer?

































Ink Yield A4 document: 600 nk Yield Ink 44 document: 400 A4 do

Ink Yield A4 document: 2 Ink Yiel

nk Yield 4 document: 259 'x6" photo: 83 k Yield In. document: 760 A4 :6" photo: 367 4":

Ink Yield Ink A4 document: 474 A4 di 4"x6" photo: 225 4"x6 ield ument: 237 ihoto: 108

Ink Yield A4 document: 824 4"x6" photo: 322

Ink Yield A4 document: 514 4"x6" photo: 199 Ink Yield A4 document: 2

Ink Yield A4 document: 6360 4"x6" photo: 858

Ink Yield 3120 A4 document: 1505 520 4"x6" photo: 231





Technical Specifications

PIXMA HOME OFFICE TS6260

	Type		Permanent
			Total 4,096 nozzles
Print Head / Ink	Number of Nozzles		(PGBK 1,024 nozzles, BK/Y each 512 nozzles, C/M each 1,024 nozzles)
	Ink Tank		5-color(C/M/Y/BK/PGBK)
Maximum Printing Resolution			4800 (horizontal) 2 x 1200 (vertical) dpi
Print Speed	Document : Col ³	ESAT/Simplex	approx. 10.0 ipm
	Document : B/W ³	ESAT/Simplex	approx. 15.0 ipm
	Photo (4"x6") ^{*3}	PP-201/Borderless	approx. 21 sec.
Printable Area	Borderless Printing ^{*4}		Top/Bottom/Right/Left margin: each 0 mm
	Bordered Printing		Top margin: 3 mm, Bottom margin: 5 mm, Left/Right margin: each 3.4 mm (LTR/LGL: Left: 6.4 mm, Right: 6.3 mm)
	Bordered Auto 2-sided printing		Top margin: 5 mm, Bottom margin: 5 mm, Left/Right margin: 3.4 mm (LTR: Left: 6.4 mm, Right: 6.3 mm)
Support Media	Rear Tray		Plain Paper, Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus Glossy II (PP-301), Matte Photo Paper (MP-101), Photo Paper Glossy (GP-701) High Resolution Paper (HR-101N),T-Shirt Transfer, Envelope, Photo Paper Plus Semi-gloss (SG-201), Greeting Card (manufactured by Avery and RedRiverPaper), Cardstock(manufactured by Neenah Paper and INKPRESS), Restickable Photo Paper (RP-101) Magnetic Photo Paper (MG-101)
	Cassette		Plain Paper
Paper Size	Rear Tray		A4, A5, B5, LTR, LGL, 4"x6", 5"x7", 7"x10", 8"x10", Envelopes(DL, COM10), Square (5" x 5", 4"x4", 3.5"x3.5"), Card Size(91 x 55mm)
	Cassette		A4, A5, B5, LTR
Paper Size (Borderless)	*Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers		A4, LTR, 4"x6", 5"x7", 7"x10", 8"x10", Square(5"x5",4"x4",3.5"x3.5"), Card Size(91 x 55mm)
	Rear Tray	Plain Paper (LTR size)	Plain Paper =100
Paper Handling		Plain Paper (A4 size)	Plain Paper, Canon Red Label Superior =100, Canon Oce Office Colour Paper =80
(Maximum Number)	Cassette	Plain Paper (LTR size)	Plain Paper =100
		Plain Paper (A4 size)	Plain Paper, Canon Red Label Superior =100, Canon Oce Office Colour Paper =80
Support Media for Auto 2-sided printing	Туре		Plain Paper
	Size		A4, A5, B5, LTR
Paper Weight	Rear Tray Cassette		Plain Paper: 64-105 g/m², Canon specialty paper: max paper weight : approx. 300 g/m² (Photo Paper Pro Platinum PT-101) Plain Paper: 64-105 g/m²
Ink End Sensor	Cusselle		Dot count
Print Head Alignment			Manual
Fax functionality			No





	Scanner Type		Flatbed
	Scanning Method		CIS
	Optical Resolution ^{*6}	*Optical resolution scan is available, only when you use TWAIN Driver.	1200 x 2400 dpi
SCAN*5	Scanning Bit Depth	Grayscale	16bit/8bit
₹	(Input/Output)	Color	
й	(Input/Output)		RGB each 16bit/8bit
	Line Scanning Speed ^{*8}	Grayscale	1.5 ms/line (300dpi)
	Line Seaming Speed	Color	3.5 ms/line (300dpi)
		Flatbed	A4/LTR(216 x 297mm)
	Maximum Document Size	ADF	N/A
	Maximum Document Size		A4/LTR
	Image Quality		3 positions (Draft, Standard, High)
ձ	Density Adjustment		9 positions, Auto intensity(AE copy)
СОРҮ		Document	approx. 19 sec.
O	Copy Speed ^{*10}		approx. 6.5 ipm
	Multiple Copy	Black/Color	max. 99 pages
	Protocol		TCP/IP
	Mina el LANI	Network Type	N/A
	Wired LAN	Data Rate	N/A
		Network Type	IEEE802.11n/IEEE802.11g/IEEE802.11b
		Frequency Band	2.4GHz
>		Channel	1-13
Ž	Wireless LAN	Range	indoor 50m (depends on the transmission speed and conditions)
_			WEP64/128bit
		Security	WPA-PSK(TKIP/AES)
			WPA2-PSK(TKIP/AES)
	Direct connection(Wireless		Available
	LAN)		
	Bluetooth		Available
	AirPrint		Available
	Windows 10 Mobile		Available
	Mopria		Available
ည	Google Cloud Print		Available
Printing Solutions	Canon Print Service (for Android)		Available
So	PIXMA Cloud Link	from smartphone or tablet	Available
ng	Common DDINT Indiant/CELDLIN	from printer	Available
Printi	Canon PRINT Inkjet/SELPHY (for iOS/for Android)		Available
	Camera Direct Spec.	Compatible Digital Camera	"PictBridge" compliant digital cameras, camcorders and camera phones
		Connecting type	WLAN
		File Format	JPEG (Exif ver2.2/2.21/2.3 compliant)*18, PNG
	Operation Panel	Display	LCD (3.0 inch / 7.5 cm TFT color/Touch)
	ADE	Paper Handling (Plain Paper)	N/A
	ADF	Auto Duplex	N/A
	Interface	USB B Port	Hi-Speed USB
		Card Slots	N/A
		Wireless LAN	Available
v	PictBridge	LAN	N/A
<u>.</u>		USB	N/A
ä	Quiet Mode	27	Available
, i	Acoustic Noise (PC Print)	Plain Paper(A4, B/W)*27	Approx. 49.0 dB(A)
)ec	Power	OFF	AC 100-240V 50/60Hz
LS.	Power Consumption	OFF Standby (scanning lamp is off)	Approx. 0.2 W
D.G		USB connection to PC	Approx. 0.8 W
General Specifications		Standby (all ports connected,	
ŏ	Tower Consumption	scanning lamp is off) Copying 28	Approx. 1.7 W
		USB connection to PC	Approx. 14 W
		Factory configuration	Approx. 372 x 315 x 139 mm
	Dimension(WxDxH)	Paper installed (cassette)	Approx. 372 x 360 x 139 mm
	,	Output/ADF trays extended	Approx. 372 x 651 x 300 mm
	Weight	kg	Approx. 6.2 kg





- *2: Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- 3: Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/IJS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type

- raper rus disasy in an advantage of the control of paper used etc.

 5: TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

 6: Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

 8: The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.

 10: Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

 11: Can be used by attaching the adapter that is separately sold in the market.
- 12: Resolution may be changed between Direct print and printing from PC.
 14: It is NOT supported via Network.
 15: The amount of image extension beyond the paper cannot be adjusted.

- *16: Plain paper is printed bordered automatically, regardless of the camera settings
- 17: Not supported for disk label print.

 18: Image data taken by DCF (Ver.1.0/2.0)-compliant digital cameras, camcorders or camera phones and recorded in JPEG (Exif-compliant) format. *19: Function depends on the connected digital cameras, camcorders or camera phones
- 20: Only 'high' mode available as for the printer without LCD.
 *23: "Non-support for 2/4/9/16-up in sticker printing as well as date/file number printing in disc label printing. As for '4-up' print layout, either file number or date can be printed at one time." *24: The performance of the printer may be reduced under certain temperature and humidity conditions.
- "25: For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.

 "26: When printing ISO/JIS-SCID N2 on 4"x6" Photo Paper Plus Glossy II using default settings.

 "27: Acoustic Noise is measured based on ISO7779 standard with default setting.

- *28: Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. Specifications are subject to change without notice.

 *29: 111 in US, CND, LTN, BRA, TW and HK.

 *31: Black & white document fax transmission speed is based on default setting using ITU-T No.1chart. Color document fax transmission speed on default setting using Canon Color Fax Test Sheet. Actual transmission

- speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.

 "32: Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.

 "33: Not supported for AirPrint.

 "34: Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program '35: Not supported for 'Printable Nail Stickers'.



