





Compact and reliable 4K ENG camcorder

The XA40 professional-use camcorder achieves high mobility which is required for on-location videography in fields such as broadcasting, reporting, documentary and event shooting. The XA40 is capable of capturing 4K video while the compact and lightweight product realizes superb mobility and operability ideal for both professional and enthusiast videographers.

The XA40 features a 1/2.3-inch CMOS sensor, a 20x optical zoom lens and a DIGIC DV 6 image processor, all in a compact and lightweight body measuring approximately 109 mm (W) x 84 mm (H) x 182 mm (D) and weighing approximately 730 g[†]. In addition to 4K/30p video capture across the entire zoom range of 29.3 mm at the wide-angle end to 601 mm at the telephoto end[†], the XA40's Over Sampling HD Processing function effectively utilizes data acquired by the 4K imaging sensor to record full HD video at an even higher image quality.

* 35 mm film equivalent. When Dynamic Mode image stabilization is OFF.





[†] Including grip belt

Technical Specifications

Soncor		1/2.3-inch 4K UHD CMOS sensor
Sensor		1/2.3-Inch 4K OHD CMOS sensor
Lens	Zooming ratio, focal length (35 mm camera equivalents)	20x optical zoom, approx. 29.3 - 601mm (4K UHD vibration control off/standard IS on)/ approx. 30.5 - 627mm (FHD vibration control off/standard IS on)
	Aperture	8-bladed circular aperture
	Image Stabilizer	Optical + electronic correction
Infrared camera supported		YES
Monitor		3.0-inch (approx. 0.46 million dots), LCD, Capacitive touch panel
EVF		0.24-inch (equivalent to approx. 1.56 million dots)
Movie recording	AVCHD recording	NO
	MP4 recording	YES
	XAVC	NO
	MOV	NO
	DV	NO
	Simultaneous Recording	YES
Recording media		SD card (2 slots)
Terminals for commercial applications	SDI terminal	NO
	GENLOCK, TC(In/Out)	NO
	XLR terminal (INPUT1/INPUT2)	YES
	Headphone terminal	YES
	USB terminal	YES
	Microphone terminal	YES
	HDMI terminal	YES
	Remote terminal	YES
Manual control ring		YES: Lens ring (function switched between zoom and focus)
Detachable Handle		YES
Wi-Fi		NO
GPS		NO (Accessories supported)
Lens hood		YES (with barrier)
Dimensions		131 x 180 x 231 mm
	Body only	Approx. 735 g
Weight	Lens hood, BP-820 and memory card (1 pc) included	Approx. 1125 g





Accessories



Tele Converter TL-H58



Wide Attachment WA-H58



Filter (58mm) PROTECT ND8xL ND4xL



Video Light VL-10Li II



GPS Receiver GP-E2



Shoulder Strap SS-600/SS-650



Battery Pack BP-828



Wrist Strap WS-20



Soft Carrying Case SC-2000



USB Cable IFC-400PCU



High Speed HDM Cable HTC-100



Remote Controller RC-V100



Battery Charger CG-800D



Battery Pack BP-820